

100 EFI Portable Breathing Compressor



Features :

- Ready to plug in and come with a cable, plug and start/stop switch
- Ideal for small application or occasional filling operations
- 1 filling hose with filling valve and pressure gauge
- 200/300 bar switch over device
- Capacity : 100 litre/minute
- Max. pressure : 330 bar

BD 2100 SCBA



Features :

- A reliable economy model breathing apparatus to suit fire fighting and industry applications
- Designed for work and rescue, suitable for asia people and comfortable
- Configuration solid and simple nylon back plate, certificate GA 124-2004
- Applications : chemical, fire fighting, foundries and metal production, mining, oil, and gas. Etc
- Include full face mask, demand regulator, carbon composite cyl. 6.8L, 300 bar, and carrying case

Air Go Pro



Features :

- Single line technology delivers medium and high pressure using just one hose
- Long strap for one or two cylinders, rubber cylinder retainer and divider keep cylinders in place
- Air go backplate is ergonomically designed to keep weight close to the body's centre of gravity
- EN 137:2006 standard
- Include full face mask, demand regulator, carbon composite cyl. 6.8 L, 300 bar, and carrying case

Motion Scout KT-Series



Features :

- Extremely simple to use
- Sensitive, electronic motion sensor recognize all normal body movements
- Maintenance free and durable
- Can be activated manually
- Suitable for fire and rescue operations, tunnel surveying and many more industrial applications

Transaire 5 and Transaire 10



Features :

- 5 or 10 minutes duration
- Deliver a consistent air supply at 40lpm (liters per minute)
- Lightweight aluminium cylinders can withstand exposure to temperatures from 0° to 160°F
- Custom air V escape respirator available

AirGo Compact SCBA Complete W/3S-PS



Features :

- Specifically designed for emergency response and escape
- The demand valve is directly attached to the pressure reducer, allowing quick donning
- High quality materials for maximum safety and durability
- EN 137:2006 [2] approved for all applications



Evolution 5200 Thermal Imaging Camera



MD-59 Evolution 5200 Thermal Imaging Camera

- High performance safety : 320°F high sense mode range gives high image definition
- Over the widest temperature range of any fire service TIC.
- Twice the low sensitivity in the 320° to 1000°F range
- 3.5" display
- Range matches 80% of the temperature range in most structural fires.
- Low cost - high value
- Heat seeker plus color detail
- Can be connected with evolution 5000 series video capture system to record in video format for documentation and training purposes.

AirXpress Industrial SCBA Complete Set



Features :

- Rugged shock resistant gauge
- Ergonomic AirXpress carrier made with glass fibre reinforced polyamid to withstand high heat and flames
- Comes with 300 bar composite compressed air cylinders and 3S-PS full face mask
- EN 137:2006 [2] approved for all applications



BREATHING SYSTEM AND SPECIAL SAFETY APPLICATION

► 92760 Portable Air Filter and Regulator



BREATHING SYSTEM, SPECIAL SAFETY
APPLICATION AND GAS DETECTOR



►

